

SPECIFICATIONS FOR OFF-ROAD FORESTRY TRAILERS

	900R	FOR1005	FOR1205	FOR1207	FOR1610	FOR2005	FOR2205	FOR2207	FOR2209	FOR2610
WEIGHT	535 lb	980 lb	1400 lb	1430 lb	1950 lb	995 lb	1185 lb	1565 lb	1645 lb	1907 lb
CAPACITY (GVWR)	3500 lb	3T / 6614 lb	5T / 11 023 lb	7T / 15 432 lb	12T / 26 456 lb	3T / 6614 lb	5T / 11 023 lb	7T / 15 432 lb	9T / 19 842 lb	12T / 26 456 lb
RECOMMENDED FOR	VTT	Tractor 30hp	Tractor 50hp	Tractor 75hp	Tractor 100hp	Tractor 30hp	Tractor 40hp	Tractor 50hp	Tractor 75hp	Tractor 100hp
OVERALL LENGTH	161"	173"	200"	200"	200"	190"	190"	211"	211"	240"
OVERALL WIDTH	54"	62"	73"	80"	80"	65½"	65½"	84½"	84½"	84"
COUPLER HEIGHT	13"	15"	15"	15"	15"	12"	12"	14"	14"	15"
HEIGHT OF POSTS	25"	41"	41"	41"	41"	41"	41"	42"	42"	42"
LOADING LENGTH	93"	112"	128"	128"	176"	120"	120"	141"	141"	170"
LOADING WIDTH	38"	55"	60"	66"	66"	60"	60"	73"	73"	73"
BASE WIDTH	23 ½"	30"	34"	40"	40"	30"	30"	44"	44"	44"
TRACK CENTER/CENTER	44"	54"	62¾"	69½"	69½"	56½"	56½"	68½"	68½"	69"
LENGTH TO THE ROCKERS	115"	138"	156"	156"	239"	147½"	147½"	148"	148"	160"
AXEL ROCKET	1½"	2"	2"	2"	2"	2"	2"	2"	2"	2"
HUB HOLES	5 HOLES	6 HOLES	6 HOLES	6 HOLES	8 HOLES	6 HOLES	6 HOLES	6 HOLES	6 HOLES	8 HOLES
AGRICULTURAL TIRES	25X12X10	11L15 8 ply	11L15 8 ply	12,5L15 10 ply	14L16.1 12 ply	11L15 8 ply	11L15 8 ply	12L15 10ply	12L15 10ply	14L16 12ply
SUPPORT	CRIC	STD	STD	STD	STD	ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION	ADJUSTABLE POSITION
TANDEM	AJUSTABLE	FIX	FIX	FIX	FIX	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS	3 ADJUSTABLE POSITIONS
GROUND CLEARANCE	14"	14"	17"	17"	20"	21"	21"	23"	23"	24"
ELECT OR HYDR. BRAKES	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	12"	12"	12"	12"	12"
WHEEL DEFLECTOR	N/A	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
OVERALL HEIGHT						64"	64"	71"	71"	73"
GRID WIDTH						57"	57"	72"	72"	72"
GRID CLEARANCE						70"	70"	70"	70"	70"
SUPPORT CLEARANCE						31"	31"	31"	31"	31"
GRID HEIGHT						43"	43"	49"	49"	49"