

HAKKIPIILKE[®]

50 Pro

+ HAKKICUT[™]
HAKKISPLIT[™]

The Hakki Pilke 50 Pro was designed in close cooperation with firewood professionals. It has been tested with a variety of wood types across the globe to ensure international viability as a professional-grade machine for industrial firewood production and consistently superior performance in all conditions.

The machine comes as standard with a wide range of features that improve efficiency and facilitate work. The HakkiCut[™] sawing interface makes using the machine fast and ergonomic. Sawing is performed at the press of a button, and the splitting and feeding mechanisms are controlled with a joystick. During cutting, the lowering speed of the saw bar is automatically adjusted according to the resistance, ensuring a fast and efficient process.

The standard equipment also includes the delay-free HakkiSplit[™] splitting system, AC10 automatic chain tensioner, cleaning out-feed conveyor and adjustable work platform.



50 Pro is equipped with patented AC 10 automatic chain tensioner. Always correct chain tension makes cutting efficient and extends the chain and bar life remarkably.

- SIGNIFICANTLY FASTER SPLITTING CYCLE THAN COMPETITION
- NO V-BELTS OR MECHANISMS THAT ARE SUBJECT TO WEAR
- LOW MAINTENANCE NEEDS

50 PRO

⊗	470/19 MM/IN
⊔	600/24 MM/IN
⊕	30 T



TECHNICAL SPECIFICATIONS

Max log diameter	470 mm	19"
Max log length	600 mm	24"
Maximum splitting power	30 t	
Bar	20"	
Power source	PTO, sm, combi	
Splitting blade	6-way	
Outfeed conveyor length	4 m	13'1"
Outfeed conveyor width	400 mm	16"
Infeed conveyor (width x length)*	0.3 x 2.85 m	12"x 9'4"

STANDARD EQUIPMENT

- Infeed serial connection kit + valve
- Accessory valve
- Hydraulic infeed conveyor
- Additional hydraulic infeed roller
- Infeed guide plate
- Hydraulic log clamp
- Safety cover
- AC10 automatic chain tensioner (hydraulic)
- HakkiCut[™] cutting control
- Automatically optimised saw lowering speed
- Automatic chain oil lubrication
- Hydraulically retracted log measuring device
- Hydraulic height adjustment of the splitting blade
- HakkiSplit[™] delay-free splitting (3 speeds)
- Hydraulic vertically and laterally pivoting outfeed conveyor
- Outfeed conveyor speed control + reversal
- Cleaning outfeed conveyor
- Oil cooler
- Adjustable work platform

DIMENSIONS IN TRANSPORT POSITION

Height	2,900 mm	9'6"
Length	3,100 mm	10'2"
Width	1,520 mm	5'0"
Weight	2,200 kg	4,850 lbs

ACCESSORIES

Splitting blade	2/4, 8, 12-way
Output conveyor extension	1 m 39"
Blower sawdust removal (TR)	
Oil heater	
HakkiFeed	422, 471, 472
Hakki Pilke Cleaner	
Hakki Pilke Roller	
Powerpack	



Replacing the splitting blade is fast and safe thanks to the detachable winch.



Easy-to-use control panel where infeed, cutting and splitting are all controlled with just one joystick.