## HAKKIPILKE® Raven 33



The Hakki Pilke Raven 33 is a reliable and easy-to-use firewood processor. The machine's direct drive hydraulics enable simultaneous functions with effortless motions of the operating lever. The robust structure and minimal need for maintenance ensure that the machine is cost-efficient to use. Effortless operation and sufficient splitting power enable the processor to split even the largest of logs – get ready to make firewood for all purposes with unparalleled ease.

The single-piece cover, which is linked with the machine's operation and equipped with gas shocks, ensures safe operation and easy saw chain maintenance. It can also be easily opened in the event of malfunctions. The low power requirement and weight enable the machine to be used with lighter equipment. The Raven 33 comes as standard with belt feed and a laterally pivoting hydraulic outfeed conveyor.

Accessories can be used to equip the firewood processor for every need. A log lifter and various log tables can be used to reduce the work load even further. The 6-way splitting blade turns even the sturdiest of logs into conveniently sized firewood. The infeed conveyor reverse valve can be used to feed and reverse logs regardless of the machine function. The features of the Raven 33 firewood processor make it a perfect fit for shared use.

- ROBUST STRUCTURE
   AND MINIMAL NEED FOR
   MAINTENANCE
- SAFE TO USE
- THE MACHINE CAN BE EQUIPPED FOR EVERY NEED



Comes with a hydraulically pivoting outfeed conveyor as standard.

## **TECHNICAL SPECIFICATIONS**

| LECHNICAL SPE                        | ыгіьмі                      | IUN      |
|--------------------------------------|-----------------------------|----------|
| Max log diameter                     | 330 mm                      | 13"      |
| Max log length                       | 500 mm                      | 20"      |
| Maximum splitting power              | 6 t                         |          |
| Bar                                  | 15"                         |          |
| Power source                         | PTO, electric               |          |
| Splitting blade                      | 2/4-way                     |          |
| Outfeed conveyor length              | 4 m                         | 13′1″    |
| Infeed conveyor length               | 2.2 m                       | 7′2″     |
| STANDARD EQUIPMENT                   |                             |          |
| Hydraulic infeed conveyor            |                             |          |
| Safety cover                         |                             |          |
| Automatic chain oil lubrication      |                             |          |
| Automatic speed valve                |                             |          |
| Pivoting outfeed conveyor            |                             |          |
| Infeed conveyor reverse valve        |                             |          |
| Cleaning outfeed conveyor            |                             |          |
| DIMENSIONS IN TRANSPO                | RT POSITIOI                 | V        |
| Height                               | 2,450 mm                    | 8'0"     |
| Length                               | 2,500 mm                    | 8'2"     |
| Width                                | 1,200 mm                    | 3′11″    |
| Weight                               | 820 kg                      | 1,808 lb |
| OPTIONAL EQUIPMENT                   |                             |          |
| Infeed serial connection kit + valve |                             |          |
| Accessory valve                      |                             |          |
| Infeed guide plate                   |                             |          |
| Splitting blade                      | 6-way                       |          |
| Outfeed conveyor extension           | 1 m                         |          |
| Outfeed conveyor speed control       |                             |          |
| Heater for oil                       |                             |          |
| Toolbox                              |                             |          |
| ACCESSORIES                          |                             |          |
| HakkiLift                            | Raven *                     |          |
| HakkiFeed                            | 371<br>(422, 471 and 472) * |          |
| Hakki Pilke Cleaner                  |                             |          |
| Hakki Pilke Roller                   |                             |          |
|                                      |                             |          |

<sup>\*</sup> requires an additional valve



Infeed conveyor reverse valve available as standard.



Log feed using a heavy duty belt with a rough surface.



Outfeed conveyor speed control valve as easy-to-install accessory.

